BSLight



UFO SMD LED IP65 LOW BAY LIGHT



APPLICATION

Ideal for Warehouse Lighting, Factory Lighting, Exibition Hall, Stadium Lighting.








Luminous Intensity Distribution Diagram




- Long Life LED Chips
- Universal Voltage 100 ~ 265V 50/60Hz
- Operating Temp. $-20^{\circ}\text{C} \sim 50^{\circ}\text{C}$
- Aluminium Die-casting Housing
- 90° Beam Angle Available
- 0.95PF
- 6KV Surge Protection
- IP65 rating fully dust tight & protected against solid objects (suitable for cool-room & oily base environment)





Available to add-on the reflector option











Model	Power (W)	ССТ (К)	CRI	Lumen (lm)	PF	IP	Life Time	Size - D x H (mm)	Net Weight	Packing
BSHBIP65-100	100W	4000/6500	>70	13000	0.95	65	50,000 H	Ø290 x 118	2.0 kg	1/CTN
BSHBIP65-150	150W	4000/6500	>70	19500	0.95	65	50,000 H	Ø345 x 127	3.1 kg	1/CTN
BSHBIP65-200	200W	4000/6500	>70	26000	0.95	65	50,000 H	Ø400 x 145	3.4 kg	1/CTN

Remark *: For CCT(K) 3000K need to be pre-order in advance.